



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	03/28/2017
Project:	Type:
Prepared By:	

DESCRIPTION

The SLWLED wide strip series is suitable for general purpose lighting in a wide variety of environments, such as commercial, industrial, retail or warehouse lighting applications.

HOUSING

Hot-dipped galvanized steel housing
Painted After Fabrication (PAF)- safe handling and added corrosion resistance
Continuous row mounting capability using a chase nipple
Numerous knockouts for easy installation
End Cap Knockout can be removed for architectural appearance.*

ELECTRICAL DETAILS

Dimming is Low Voltage (0-10v)
Driver Details (per driver)
Input Voltage : 120-277V
Input Current Max : .77 @ 120V / .33 @ 277V
Input Frequency : 50/60Hz
Power Factor : >0.95
THD : < 20%
Min Operating Temp : -40°C
Wattage : 92W
Board Details (per board)
CRI : > 80
Color Consistency : <3.5
Voltage @ 55°C @ 65mA : 43.8

NEC required ballast disconnect pre-installed

LISTINGS/RATINGS/COMPLIANCE

Fixtures are UL listed and suitable for damp locations.

Fixtures are DLC listed and featured of the Qualified Products List (QPL).**

WARRANTY

Guaranteed for five years from the purchase date of the product against mechanical defects in manufacturing

OPTIONS

This fixture may be suspended via optional cable hanging kit.

NOTES

Product performance may vary depending on model and end user environment.

*Consult factory for ordering instructions.

**Not all product variations meet Design Light Consortium Qualifications. Please verify that the product is listed on the DLC products list at www.designlightconsortium.org/QPL.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

SLWLED Series

LED Strip Wide



SPECIFICATIONS / DIMENSIONS

2'
Width: 4 1/2" Height: 3 7/8" Length: 24"
4'
Width: 4 1/2" Height: 3 7/8" Length: 48"
8'
Width: 4 1/2" Height: 3 7/8" Length: 96"

- More Information Continues on next page -



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
 tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	03/28/2017
Project:	Type:
Prepared By:	

ORDERING INFORMATION

Sample Part Code: **SLWLED4-4400D1L840**

SLWLED				L8		
SERIES	LENGTH	LUMEN OUTPUT	NO. OF DRIVERS	CRI	COLOR TEMP	OPTION
SLWLED	[2]: 2ft [4]: 4ft [8]: 8ft	[2200]: 2200 lumens [3300]: 3300 lumens [4400]: 4400 lumens [5280]: 5280 lumens [6600]: 6600 lumens [8800]: 8800 lumens [14000]: 14000 lumens [17600]: 17600 lumens [21200]: 21200 lumens	[D1]: 1 Driver [D1S]: 1 Driver - Down Center [D2]: 2 Drivers [D4]: 4 Drivers	[L8]: CRI±85	[30]: 3000k [35]: 3500k [40]: 4000k [50]: 5000k	[BLANK]: No Options [B500]: 500 Lumen LED emergency backup [B1000]: 1000 Lumen LED emergency backup [W1]: 6ft Whip