

CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLCR45040K-UN4

SERIES SPECIFICATIONS




To supply and install TamLite Tlcr series of LED Wrap fixtures as specified. The luminaire shall operate at 347VAC. The housing shall be constructed of powder-coated aluminum with a heat and impact resistant tempered PMMA lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-UL-us listed and DLC Qualified.



PERFORMANCE SPECIFICATIONS

FIG. 1 - Luminance Distribution Chart



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLCR45040K-UN4

PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 4717.50 lm
Efficacy: 102.27 lm/W
Operating Temp: -20°C to +40°C

Environmental Rating: IP20
Certification Standards: cULus, DLC

Anti-Corrosion Warranty: 5 Years
Limited Product Warranty: 5 Years

LED SPECIFICATIONS

LED Type: Array
CRI: 81.0
R9: 6

Average Life: $L_{70} = >50,000$ hrs
Colour Temperature: 4000K
Chromaticity: $x = 0.4299; y = 0.4039$

Dimming: 1-10V
Duv: 0.0009

ELECTRICAL SPECIFICATIONS

Voltage: 347VAC
Frequency: 60 Hz
Fixture Draw: 46.13W

Current Draw: 0.1396A
Power Factor: 0.9524

THD (%): 12.58%
Driver: Antron


PHYSICAL SPECIFICATIONS

Colour(s): White
Finished Type: Textured Powder Coat over Chromate Conversion Coat

Wiring: Luminaire Disconnect
Mounting: Surface, Suspended
Housing Material: Die-Cast Aluminum

Lens Material: Acrylic
Lens Type: Frosted Prismatic

LINE DRAWING



ORDERING INFORMATION

Part Number: TLCR45040K-UN4

Box Quantity: 1

Box Length: 1210mm - 47.64"

Box Height: 73mm - 2.87"

Box Width: 213mm - 8.39"

Carton Quantity: 6

Carton Length: 1230mm - 48.43"

Carton Height: 235mm - 9.25"

Carton Width: 385mm - 15.16"