

CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLHBL24050K-UN4

## SERIES SPECIFICATIONS




To supply and install Tamlite TLHBL series of LED Highbays as specified. The luminaire shall operate at 347VAC. The housing shall be constructed of powder-coated aluminum with a heat and impact resistant tempered PMMA lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-UL-us listed and DLC Qualified.



## PERFORMANCE SPECIFICATIONS

FIG. 1 - Luminance Distribution Chart



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLHBL24050K-UN4

## PERFORMANCE SPECIFICATIONS

**Initial Lumen Output:** 30740.00 lm  
**Efficacy:** 136.39 lm/W  
**Operating Temp:** -20°C to +40°C

**Environmental Rating:** IP20  
**Certification Standards:** cULus, DLC

**Anti-Corrosion Warranty:** 5 Years  
**Limited Product Warranty:** 5 Years

## LED SPECIFICATIONS

**LED Type:** Array  
**CRI:** 83.4  
**R9:** 10

**Average Life:**  $L_{70} = >50,000$  hrs  
**Colour Temperature:** 5115K  
**Chromaticity:**  $x = 0.3423; y = 0.3537$

**Dimming:** 1-10V  
**Duv:** 0.0022

## ELECTRICAL SPECIFICATIONS

**Voltage:** 347VAC  
**Frequency:** 60 Hz  
**Fixture Draw:** 225.38W

**Current Draw:** 0.6580A  
**Power Factor:** 0.987

**THD (%):** 8.31%  
**Driver:** Antron


## PHYSICAL SPECIFICATIONS

**Colour(s):** White  
**Finished Type:** Textured Powder Coat  
 over Chromate Conversion Coat

**Wiring:** Luminaire Disconnect  
**Mounting:** Surface, Suspended  
**Housing Material:** Die-Cast Aluminum

**Lens Material:** Polycarbonate  
**Lens Type:** Clear

## LINE DRAWING



## ORDERING INFORMATION

**Part Number:** TLHBL24050K-UN4

**Box Quantity:** 1

**Box Length:** 1195mm - 47.05"

**Box Height:** 80mm - 3.15"

**Box Width:** 345mm - 13.60"

**Optional Extras:** TLHB-C10 (10FT SOOW Cord)