

CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLNR22040K-UN4

## SERIES SPECIFICATIONS




To supply and install TamLite TLNR series of LED Wrap fixtures as specified. The luminaire shall operate at 347VAC. The housing shall be constructed of powder-coated aluminum with a heat and impact resistant tempered PMMA lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-UL-us listed.



## PERFORMANCE SPECIFICATIONS

FIG. 1 - Luminance Distribution Chart



<b>CONTRACTOR:</b>	
<b>PROJECT:</b>	<b>DATE:</b>
<b>PREPARED BY:</b>	<b>MODEL#:</b> TLNR22040K-UN4

## PERFORMANCE SPECIFICATIONS

**Initial Lumen Output:** 2451.20 lm  
**Efficacy:** 116.60 lm/W  
**Operating Temp:** -20°C to +40°C

**Environmental Rating:** IP20  
**Certification Standards:** cULus

**Anti-Corrosion Warranty:** 5 Years  
**Limited Product Warranty:** 5 Years

## LED SPECIFICATIONS

**LED Type:** Array  
**CRI:** 81.1  
**R9:** 2

**Average Life:**  $L_{70} = >50,000$  hrs  
**Colour Temperature:** 4000K  
**Chromaticity:** x= 0.4418; y= 0.4095

**Dimming:** 1-10V  
**Duv:** 0.0015

## ELECTRICAL SPECIFICATIONS

**Voltage:** 347VAC  
**Frequency:** 60 Hz  
**Fixture Draw:** 21.02W

**Current Draw:** 0.0648A  
**Power Factor:** 0.9349

**THD (%):** 11.48%  
**Driver:** Antron


## PHYSICAL SPECIFICATIONS

**Colour(s):** White  
**Finished Type:** Textured Powder Coat over Chromate Conversion Coat

**Wiring:** Luminaire Disconnect  
**Mounting:** Surface, Suspended  
**Housing Material:** Die-Cast Aluminum

**Lens Material:** Acrylic  
**Lens Type:** Frosted Prismatic

## LINE DRAWING



## ORDERING INFORMATION

**Part Number:** TLNR22040K-UN4

**Box Quantity:** 1

**Box Length:** 640mm - 25.20"

**Box Height:** 100mm - 3.94"

**Box Width:** 80mm - 3.15"

**Carton Quantity:** 24

**Carton Length:** 1220mm - 48.03"

**Carton Height:** 345mm - 13.58"

**Carton Width:** 315mm - 12.40"