

CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLPS223640K-UNV-WH

SERIES SPECIFICATIONS

To supply and install TamLite's TLPs Series of LED Panel fixture as specified. The Luminaire shall operate at 120VAC to 277VAC and use an Everlight Approved Driver. The frame shall be constructed of Painted Aluminium with a PMMA diffuser. LEDs shall be as specified Everlight 67-21S LED chips. The luminaire shall be c-UL-us listed



PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 4554.51 lm
Efficacy: 127.22 lm/W
Operating Temp: -20°C to +40°C

Environmental Rating: IP20
Certification Standards: cULus
Limited Product Warranty: 5 Years

Spacing Criteria: 1.38 (C0/180),
 1.24 (C90/270)

LED SPECIFICATIONS

LED: Everlight 67-21S
LED Type: LED
CRI: 82.1


R9: 6
Colour Temperature: 3943K
Chromaticity: x=0.3841; y=0.3822

Average Life: L₇₀= >54,000 hrs
Duv: 0.0015
Dimming: 0-10V

FIG. 4 - Colour Rendering Indices

R1	80	R9	6
R2	89	R10	74
R3	95	R11	78
R4	79	R12	57
R5	79	R13	83
R6	84	R14	97
R7	86	R15	7
R8	63		

FIG. 5 - Spectral Power Distribution



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#: TLPS223640K-UNV-WH

ELECTRICAL SPECIFICATIONS

Operating Voltage: 120-277 VAC
Frequency: 50/60Hz
Fixture Draw: 35.80W

Current Draw: 0.304A
Power Factor: 0.981 @ 120VAC;
 0.916 @ 277VAC

I-THD (%): 9.3% @ 120VAC;
 14.2% @ 277VAC


PHYSICAL SPECIFICATIONS

Colour(s): White
Finishing Type: Painted Aluminum
Wiring: Junction Box

Mounting: Recessed, Surface

Housing Material: Painted Steel
Diffuser Material: PMMA

LINE DRAWING



ORDERING INFORMATION

Part Number: TLPS223640K-UNV-WH

Carton Quantity: 2

Carton Length: 715mm - 28.15"
Carton Width: 715mm - 28.15"

Carton Height: 115mm - 4.53"
Carton Weight: 9.50kg - 20.95lbs

Optional Extras: TLP22SMK-WH, TLP22SPK-WH, TLP22EMK-UNV