

| | |
|---------------------|---------------------------|
| CONTRACTOR: | |
| PROJECT: | DATE: |
| PREPARED BY: | MODEL#: WPFLED505K |

SERIES SPECIFICATIONS



To supply and install TamLite WPF series of LED fixtures as specified. The luminaire shall operate at 120VAC to 277VAC, and use a constant current type driver. The housing shall be constructed of powder-coated die-cast aluminum with a hinged wiring compartment, and an impact resistant polycarbonate lens. A durable formed gasket shall be provided between the enclosure and the lens, and the wiring compartment and housing. Internal wiring shall terminate in quick connects for ease of connectivity. The reflector shall be made of highly specular material and contoured to maximize light output efficiency. All parts shall be corrosion resistant. LEDs shall be as specified, CREE® CXB1512 LED Chips. The LEDs shall be supplied with the luminaire. The fixture shall be c-UL-us listed and DLC Qualified.



PERFORMANCE SPECIFICATIONS

FIG. 1 - Luminance Distribution Chart




FIG. 2 - Isofootcandle Diagram




FIG. 3 - Zonal Lumen Summary

| ZONE | PERCENTAGE | ZONE | PERCENTAGE | ZONE | PERCENTAGE |
|-------|------------|---------|------------|---------|------------|
| 0-10 | 3.6% | 60-70 | 11.1% | 120-130 | 0% |
| 10-20 | 10.4% | 70-80 | 4.2% | 130-140 | 0% |
| 20-30 | 15.6% | 80-90 | 0.2% | 140-150 | 0% |
| 30-40 | 19.0% | 90-100 | 0% | 150-160 | 0% |
| 40-50 | 19.7% | 100-110 | 0% | 160-170 | 0% |
| 50-60 | 16.3% | 110-120 | 0% | 170-180 | 0% |

| | |
|---------------------|---------------------------|
| CONTRACTOR: | |
| PROJECT: | DATE: |
| PREPARED BY: | MODEL#: WPFLED505K |


PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 5046.00 lm
Luminaire Type: Type III Short
Environmental Rating: IP65
BUG Rating: B2-U0-G1

Limited Product Warranty: 5 Years
Anti-Corrosion Warranty: 5 Years
Certification Standards: cULus, RoHS, DLC

Efficacy: 107.25 lm/W
Beam Angle: 85.20°
Operating Temperature: -40°C to +40°C

FIG. 4 - LCS Graph



| WPFLED505K | | |
|-------------------------------|-------------|------------|
| | Lumens | %Luminaire |
| FL - Front-Low (0-30) | 913.33 | 18.1 |
| FM - Front-Medium (30-60) | 2386.76 | 47.3 |
| FH - Front-High (60-80) | 726.62 | 14.4 |
| FVH - Front-Very High (80-90) | 10.092 | 0.2 |
| BL - Back-Low (0-30) | 580.29 | 11.5 |
| BM - Back-Medium (30-60) | 383.50 | 7.6 |
| BH - Back-High (60-80) | 45.414 | 0.9 |
| BVH - Back-Very High (80-90) | 5.046 | 0.1 |
| UL - Uplight-Low (90-100) | 0 | 0.0 |
| UH - Uplight-High (100-180) | 0 | 0.0 |
| TOTAL | 5046 | 100 |

ELECTRICAL SPECIFICATIONS

Voltage: 120-277VAC
Driver: Meanwell
Fixture Draw: 47.05W @ 120VAC;
 47.58W @ 277VAC

Current Draw: 0.4000A @120VAC;
 0.1889A @277VAC
Power Factor: 0.9801 @120VAC;
 0.9092 @277VAC

THD: 15.96% @120VAC; 19.01%
 @277VAC
Frequency: 60 Hz

LED SPECIFICATIONS

LED Chip: CREE® CXB1512
LED Type: COB
R9: 18

Average Life: L70(6k)>36,000 hrs
Colour Temperature: 5082K
Duv: 0.0045

CRI: 84.8
Chromaticity: x=0.3436; y=0.3595


FIG. 5 - Colour Rendering Indices

| | | | | | |
|-----------|----|------------|----|------------|----|
| R1 | 84 | R6 | 85 | R11 | 82 |
| R2 | 90 | R7 | 89 | R12 | 60 |
| R3 | 93 | R8 | 71 | R13 | 85 |
| R4 | 84 | R9 | 18 | R14 | 96 |
| R5 | 83 | R10 | 74 | R15 | 79 |

| | |
|---------------------|---------------------------|
| CONTRACTOR: | |
| PROJECT: | DATE: |
| PREPARED BY: | MODEL#: WPFLED505K |

LED SPECIFICATIONS

FIG. 6 - Spectral Distribution Chart




PHYSICAL SPECIFICATIONS

Colour(s): Architectural Bronze
Finished Type: Textured Powder Coat
 over Chromate Conversion Coat

Mounting: Wall Mount/Pole Mount
Housing Material: Die-Cast Aluminum
Reflector Material: Specular Aluminum

Lens Material: Tempered Glass
Wiring: 3 x 1/2" Coin Plugs
Lens Type: Clear

LINE DRAWING



ORDERING INFORMATION

Part Number: WPFLED505K

Inner Carton Quantity: 1

Inner Carton Length: 340mm - 13.38"

Inner Carton Height: 360mm - 10.23"

Inner Carton Width: 320mm - 12.59"

Inner Carton Weight: 4.47kg - 9.85lbs

Outer Carton Quantity: 2

Outer Carton Length: 390mm - 15.35"

Outer Carton Height: 360mm - 14.17"

Outer Carton Width: 320mm - 12.59"

Outer Carton Weight: 8.5kg - 18.74lbs

Optional Extras: WPFLED-SF (Slip Fitter), WPFLED-PA (Pole Mount Arm), WPFLED-PC (Photocell)